Article No.	Description	Range	Belt thickness [mm]	Top cover thickness [mm]	Top hardness shore [Sh]	Force at 1% elongation [N/mm]	Number of plies	Flexing [mm]; (20°C)	Back flexing [mm]; (20°C)	Temperature range: Continuosly [°C]	Short [°C]	Standard width [mm]	Max. available width [mm]	Weight [kg/m2]	LN Low noise	CR Cold resistant	HD Hydrolysis resistant	AS Antistatic	HC High conductivity	FR Flame retardant	FDA	EC 1935/2004; EU 10/2011	Foodgrade	HR Heat resistant	AM Antimicrobial	ATEX	EF	AB
MATERIAL	**POLYESTER**																											
577011	Amtel EM 4/1 P17+02 ivory M2 FG AS		1,40	0,20	40 D	4	1	20	20	-20 / +110	-20 / +130	1.500	3.000	1,50				X			X	X	X				X	
577521	Amtel ESM 8/2 A18+03 ivory M2 AS FG		2,40	0,30	40 D	8	2	60	70	-20 / +110	-20 / +130	2.000	2.000	2,50				X			X	X	X				X	
577761	Amtel ESM 8/2 0+03 ivory M2 AS FG		1,90	0,30	40 D	8	2	40	60	-20 / +110	-20 / +130	2.000	2.000	2,10				X			X	X	X				X	
577841	Amtel EM04 8/2 0+04 ivory M2 FG		2,20	0,40	40 D	8	2	50	70	-20 / +110	-20 / +130	2.000	2.000	2,20							X	X	X				X	
511472	Amtel EX05 12/3 0+03 ivory M2 FG		2,90	0,45	40 D	12	3	120	160	-20 / +110	-20 / +130	1.500	3.000	3,50	X						X	X	X				X	
MATERIAL	**PVC/RUBBER**																											
513039	Elastoflex EM 8/2 00+P38 l-green AS		2,10	0,80	55 A	8	2	25	50	-15 / +80	-15 / +100	1.500	1.500	2,40				X									X	
513040	Elastoflex EM 12/3 00+P38 l-green AS	SR	3,10	1,00	55 A	12	3	50	100	-15 / +80	-15 / +100	1.500	1.500	3,50				X										X
514831	Elastoflex EM 15/3 0+A79 beige		8,80	4,00	65 A	15	3	100	120	-15 / +80	-15 / +100	1.450	2.000	7,00													X	
MATERIAL	**FABRIC**																											
511736	Fabric EC 6/2 00+0 (PU) transparent FG	SR	1,50	-	-	6	2	15	20	-30 / +80	-30 / +110	2 000	2 000	1,40									X				X	X
513682	Fabric EM/C 4/2 00+0 FG transparent		1,65	-	-	4	2	8	20	-20 / +90	-20 / +110	2000	3000	1,40							X	X	X				X	
511022	Fabric EM 8/2 0+0 (AM) ivory FG		1,60	-	-	8	2	40	40	-20 / +80	-40 / +100	1500	3000	1,70													X	
500514	Fabric EM 8/2 0+0 white AS FG	SR	1,50	-	-	8	2	20	20	-15 / +80	-15 / +100	2000	3000	1,50													X	
573630	Fabric EM/S 6/2 00+0 white /2,1 mm		2,10	-	-	6	2	20	30	-10 / +90	-15 / +100	2000	3000	2,00													X	
526311	Fabric ESF 6/2 0+0 white AS FG NL		1,30	-	-	6	2	20	20	-15 / +80	-15 / +100	2000	3000	1,30													X	
576760	Fabric EF/C 10/3 0+0 white FG NL		2,50	-	-	10	3	60	80	-15 / +80	-15 / +100	2000	2000	2,80							X	X	X				X	
515030	Fabric EM 19/3 0+0 white AS FR/FRA		3,00	-	-	19	3	90	90	-15 / +80	-15 / +100	2000	3000	3,50				X		X							X	
MATERIAL	**FELT**																											
570970	Felt EM 5/1 0+FE white FG	SR	3,00	1,70	-	5	1	30	30	-10 / +80	-10 / +100	1950	1950	1,70							X	X	X				X	
511749	Felt EM 5/1 0+FE beige		2,80	2,00	-	5	1	30	30	-15 / +80	-15 / +100	1450	1450	2,20													X	
578850	Felt EX 10/2 0+FE black AS		3,30	1,70	-	10	2	50	100	-15 / +80	-15 / +100	1970	1970	2,70	X			X									X	
577600	Felt EX 10/2 FE+FE black AS		5,00	1,70	-	10	2	80	80	-15 / +80	-15 / +100	1940	1940	4,50				X									X	
SBFE000021	Felt NPF 25 white FG		2,50	1,20	-	8		30	30	-10 / +120	-10 / +120	2000	2000	1,45							X		X				X	
SBFE000025	Felt NPF 25 black HC AS	76410	2,50	1,20	-	8		30	30	-10 / +120	-13 / +130	2000	2000	1,60				X	X								X	
SBFE000045	Felt NPF 40 black HC AS	75844	4,00	1,80	-	10		70	70	-10 / +120	-13 / +130	2000	2000	2,50				X	X								X	
SBFE000065	Felt NPF 60 black HC AS	76408	5,50	2,50	-	11		120	120	-10 / +120	-13 / +130	2000	2000	3,40				X	X								X	
MATERIAL	**PVC - smooth**																											
570551	Flexam EF 10/2 0+10 black M2 AS FR		2,50	1,00	80 A	10	2	60	100	-15 / +80	-15 / +100	3000	3000	3,30				X			X						X	
576690	Flexam EF 10/2 0+15 green FG	SR	3,10	1,50	80 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,50							X	X	X				X	
570330	Flexam EF 15/3 00+10 light blue AS FG		3,50	1,00	80 A	15	3	100	160	-15 / +80	-15 / +100	2040	2040	4,90				X			X	X	X				X	
570600	Flexam EF 30/2 00+07 green FG		3,40	0,70	70 A	30	2	120	120	-15 / +80	-15 / +100	2000	2500	4,30							X	X	X				X	
578620	Flexam EF 15/3 10+20 white AS FR FG	SR	5,90	2,00	85 A	15	3	180	240	-15 / +80	-15 / +100	2000	2000	7,50				X		X	X		X			C2		X
510453	Flexam EF 45/3 12+13 white M2 AS FG	SR	7,10	1,30	70 A	45	3	350	500	-15 / +80	-15 / +100	2000	2500	8,60				X			X		X			C2		X
575831	Flexam EM 8/2 01+03 black M2		1,90	0,30	90 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,60													X	
575760	Flexam EM 8/2 0+04 green AS FG	SR	1,90	0,40	80 A	8	2	25	50	-15 / +80	-15 / +100	2000	3000	2,10							X	X	X			C3	X	X
575910	Flexam EM 8/2 00+04 dark green AS FG		2,00	0,40	80 A	8	2	40	70	-15 / +80	-15 / +100	2000	2000	2,20				X			X	X	X			C3	X	
575911	Flexam EM 8/2 00+04 dark green M2 AS FG		2,00	0,40	80 A	8	2	40	70	-15 / +80	-15 / +100	2000	2000	2,20				X			X	X	X			C3	X	
575591	Flexam EM 8/2 00+04 green M2 AS FG		1,90	0,40	80 A	8	2	25	50	-15 / +80	-15 / +100	2000	3000	2,10				X			X	X	X				X	
575651	Flexam EM 8/2 0+05 blue M2 AS NL		2,20	0,50	70 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,50													X	
559037	Flexam EM 8/2 0+05 petrol AS FG		2,00	0,50	80 A	8	2	40	60	-15 / +80	-15 / +100	2000	2000	2,20				X									X	
512483	Flexam EM 8/2 00+04 white AS FG	SR	1,80	0,40	80 A	8	2	25	50	-15 / +80	-15 / +100	2000	3000	2,10				X			X	X	X				X	
573009	Flexam EM 8/2 00+04 light blue M1 AS FG		2,00	0,40	80 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,10				X			X	X	X				X	
575330	Flexam EM 10/2 0+07 green AS FG	SR	2,30	0,70	80 A	10	2	40	80	-15 / +80	-15 / +100	2000	3000	2,50							X	X	X				X	X
500519	Flexam EM 10/2 0+07 petrol AS		2,50	0,70	70 A	10	2	40	80	-15 / +80	-15 / +100	1500	3000	2,90				X								C3	X	
574300	Flexam EM 10/2 0+15 green FG	SR	3,10	1,50	80 A	10	2	60	100	-15 / +80	-15 / +100	2000	3000	3,50							X	X	X				X	
574930	Flexam EM 10/2 07+07 green FG		3,20	0,70	80 A	10	2	80	80	-15 / +80	-15 / +100	2000	3000	3,50							X	X	X				X	
514163	Flexam EM 10/2 07+07 dark grey M2 FG		3,20	0,70	80 A	10	2	80	80	-15 / +80	-15 / +100	2000	3000	3,50									X				X	
574831	Flexam EM 10/2 07+07 light blue M2 FG NL	limited	3,20	0,70	80 A	10	2	80	80	-15 / +80	-15 / +100	2000	3000	3,50							X	X	X				X	
514471	Flexam EM 12/2 00+07 d.green M1 AS FG		2,50	0,70	80 A	12	2	60	80	-15 / +80	-15 / +100	2000	3000	2,90				X			X	X	X				X	

Article No.	Description	Range	Belt thickness [mm]	Top cover thickness [mm]	Top hardness shore [°]	Force at 1% elongation [N/mm]	Number of plies	Flexing [mm]; (20°C)	Back flexing [mm]; (20°C)	Temperature range: Prolonged [°C]	Short [°C]	Standard width [mm]	Max. available width [mm]	Weight [kg/m2]	LN Low noise	CR Cold resistant	HD Hydrolysis resistant	AS Antistatic	HC High conductivity	FR Flame retardant	FDA	EC 1935/2004; EU 10/2011	Foodgrade	HR Heat resistant	AM Antimicrobial	ATEX	EF	AB
MATERIAL	**PVC - smooth**																											
570180	Flexam EM 15/3 0+10 green AS FG	SR	4,10	1,00	80 A	15	3	60	80	-15 / +80	-15 / +100	2000	2000	5,00				X			X	X	X				X	
510328	Flexam EM 15/3 0+20 petrol AS FG		5,00	2,00	80 A	15	3	120	200	-15 / +80	-15 / +100	1500	3000	5,70				X			X	X	X				X	
514474	Flexam EM 18/3 00+10 d.green M1 AS FG		4,00	1,00	80 A	18	3	100	160	-15 / +80	-15 / +100	2000	3000	5,20				X					X			C3	X	
574451	Flexam ES/M 6/2 0+04 black M2	SR	1,80	0,40	88 A	6	2	30	50	-15 / +80	-15 / +100	2000	2000	2,10													X	X
574851	Flexam ES/M 6/2 0+04 light grey M2	limited	1,80	0,40	88 A	6	2	30	50	-15 / +80	-15 / +100	1580	1630	2,40													X	
574731	Flexam EX 5/1 0+04 black M2 AS		1,05	0,40	88 A	5	1	20	30	-15 / +80	-15 / +100	1500	1500	1,20	X			X									X	
578491	Flexam EX 10/2 0+05 black M2 AS 2,1 mm	SR	2,10	0,50	80 A	10	2	30	60	-15 / +80	-15 / +100	2000	2000	2,60	X			X									X	
574601	Flexam EX 10/2 0+05 black M2 AS FR	SR	2,50	0,50	80 A	10	2	60	80	-15 / +80	-15 / +100	2000	3000	2,90	X			X		X						C3	X	
574711	Flexam EX 10/2 0+07 black M2 AS FR		2,50	0,70	95 A	10	2	100	100	-10 / +80	-10 / +100	2020	3000	2,90	X			X		X							X	
573230	Flexam EX 10/2 0+10 black AS FR		3,00	1,00	80 A	10	2	40	80	-15 / +80	-15 / +100	2020	2020	3,80	X			X		X							X	
573870	Flexam EX 12/3 0+20 grey AS		5,00	2,00	35 A	12	3	120	220	-25 / +80	-25 / +100	2000	2000	5,30	X			X									X	
MATERIAL	**PVC - top profile**																											
513118	Flexam EF 12/2 0+P18 black AS FR		2,50	0,90	70 A	12	2	50	90	-15 / +80	-15 / +100	3000	3000	2,80				X		X							X	
578352	Flexam EC/M 8/2 00+A54 black HC LE		2,50	1,15	80 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	2,80				X	X								X	
578353	Flexam EC/M 8/2 00+A22 black HC LE NL		2,50	1,15	80 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	2,50					X								X	
513296	Flexam EM 4/1 02+P7 black	limited	2,00	1,20	35 A	4	1	7	10	-15 / +80	-15 / +100	1500	1600	2,00													X	
500228	Flexam EM 8/2 0+P6 petrol AS	SR	5,30	3,80	35 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	4,30				X									X	
574173	Flexam EM 8/2 0+P7 petrol AS	SR	3,10	1,60	35 A	8	2	40	55	-15 / +80	-15 / +100	1500	1600	2,90				X			X	X	X				X	
574172	Flexam EM 8/2 0+A32 petrol AS	SR	2,70	1,20	35 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	3,00				X									X	
574174	Flexam EM 8/2 0+P24 petrol AS FG	SR	2,60	1,10	35 A	8	2	40	55	-15 / +80	-15 / +100	2000	3000	2,90				X			X	X	X				X	
514795	Flexam EM 8/2 00+P25/2 dark green		7,60	6,60	40 A	8	2	100	200	-15 / +80	-15 / +100	2000	3000	4,70													X	
575942	Flexam EM 8/2 00+A32 green AS FG		2,60	1,00	35 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,20				X			X	X	X			C2	X	
575962	Flexam EM 8/2 0+A34 green AS FG		4,40	2,90	35 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	3,50				X			X	X	X			C2	X	
575972	Flexam EM 8/2 00+A42 dark green AS FG		4,40	2,90	55 A	8	2	40	50	-15 / +80	-15 / +100	2000	2000	3,50				X			X	X	X			C2	X	
576942	Flexam EM 10/2 0+A42 green FG		4,70	2,90	35 A	10	2	60	140	-25 / +80	-15 / +100	2000	2000	3,80													X	
575952	Flexam EM 10/2 0+A32 Green AS/55 SH																										X	
574752	Flexam EM 15/3 0+A79 grey		7,80	4,80	55 A	15	3	120	220	-15 / +80	-15 / +100	1350	2000	6,10												C3	X	
576082	Flexam EM 19/3 00+P7 green AS FR NL		4,20	1,40	80 A	19	3	100	160	-15 / +80	-15 / +100	1600	1600	4,60				X		X							X	
513644	Flexam ES/M 8/2 0+A54 black AS		2,40	1,00	80 A	8	2	50	80	-15 / +80	-15 / +100	1524	1800	2,30				X									X	
574972	Flexam ESM 6/2 0+A21 black AS FR/35 ShA		1,85	0,50	35 A	6	2	20	30	-15 / +80	-15 / +100	2000	2000	2,30				X		X							X	
572692	Flexam EX 7/1 0+A54 black AS		1,60	1,00	70 A	7	1	40	80	-15 / +80	-15 / +100	2000	2000	1,50	X			X									X	
575252	Flexam EX 8/2 0+A20 black AS FR		7,80	6,10	55 A	8	2	80	160	-15 / +80	-15 / +100	2020	2020	5,20	X			X		X							X	
575262	Flexam EX 8/2 0+A66 black AS FR		7,80	6,30	55 A	8	2	60	100	-15 / +80	-15 / +100	2000	2000	5,20	X			X		X							X	
574122	Flexam EX 10/2 0+A32 black AS	SR	2,70	1,00	35 A	10	2	25	40	-25 / +80	-25 / +100	2000	3000	2,20	X			X									X	
578812	Flexam EX 10/2 0+A32 black AS FR		2,80	1,00	40 A	10	2	50	80	-15 / +80	-15 / +100	2000	2000	2,90	X			X		X							X	
574552	Flexam EX 10/2 0+A42 black AS	SR	4,50	2,90	55 A	10	2	50	100	-15 / +80	-15 / +100	2000	2000	3,60	X			X									X	
572652	Flexam EX 10/2 0+A42 black AS FR		4,70	2,90	55 A	10	2	40	90	-15 / +80	-15 / +100	2020	2020	4,50	X			X		X							X	
574123	Flexam EX 10/2 0+A47 black AS	SR	2,50	0,90	35 A	10	2	25	40	-25 / +80	-25 / +100	2000	2000	2,80	X			X									X	
MATERIAL	**PVC - bottom profile**																											
572410	Flexam EF 5/1 A18+06 white FG		1,80	0,60	80 A	5	1	35	50	-15 / +80	-15 / +100	2000	2000	1,80									X				X	
572400	Flexam EF 5/1 A18+06 green FG		1,80	0,60	80 A	5	1	35	50	-15 / +80	-15 / +100	2000	2000	1,80							X	X	X				X	
572470	Flexam EF 5/1 A18+06 l.blue FG		1,80	0,60	80 A	5	1	35	50	-15 / +80	-15 / +100	2000	2000	1,80							X	X	X				X	
573650	Flexam EF 10/2 A18+07 green FG	SR	3,00	0,70	80 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,20							X	X	X			C2	X	
570370	Flexam EF 10/2 A18+07 l-blue FG		3,20	0,70	80 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,40							X	X	X			C2	X	
514965	Flexam EF 10/2 A18+10 black FG		3,45	1,00	80 A	10	2	60	90	-15 / +80	-15 / +100	1500	3000	3,80							X	X	X				X	
513993	Flexam EF 10/2 A18+10 l-blue FG		3,45	1,00	80 A	10	2	60	90	-15 / +80	-15 / +100	1500	3000	3,80							X	X	X				X	
576350	Flexam EF 15/3 A18 + 07 green FG		3,90	0,70	80 A	15	3	120	120	-15 / +80	-15 / +100	2000	3000	4,20							X	X	X				X	
576340	Flexam EF 15/3 A18 + 07 l-blue FG	SR	3,90	0,70	80 A	15	3	120	120	-15 / +80	-15 / +100	2000	2000	4,20							X	X	X				X	
574030	Flexam EM 8/2 A18+05 black		2,70	0,40	80 A	8	2	40	70	-15 / +80	-15 / +100	2000	2000	3,40													X	
573030	Flexam EM 8/2 A18+05 green FG		2,70	0,50	80 A	8	2	40	70	-15 / +80	-15 / +100	2000	3000	2,70							X	X	X				X	
570950	Flexam EM 10/2 A18+07 green FG	SR	3,20	0,70	80 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,00							X	X	X				X	X
574680	Flexam EM 9/3 A18+07 green FG	SR	4,20	0,70	80 A	9	3	120	220	-15 / +80	-15 / +100	2000	2000	4,50							X	X	X				X	

Article No.	Description	Range	Belt thickness [mm]	Top cover thickness [mm]	Top hardness shore [°]	Force at 1% elongation [N/mm]	Number of plies	Flexing [mm]; (20°C)	Back flexing [mm]; (20°C)	Temperature range: Prolonged [°C]	Short [°C]	Standard width [mm]	Max. available width [mm]	Weight [kg/m2]	LN Low noise	CR Cold resistant	HD Hydrolysis resistant	AS Antistatic	HC High conductivity	FR Flame retardant	FDA	EC 1935/2004; EU 10/2011	Foodgrade	HR Heat resistant	AM Antimicrobial	ATEX	EF	AB
MATERIAL	**PVC - smooth**																											
585031	Nonex EE /1 00+05 l-blue M2 FG AM		1,60	0,50	65 A		1	14	30	-15 / +80	-15 / +80	2000	2000	1,60							X	X	X		X		X	
570060	Nonex EF 10/2 00+07 white FG		2,30	0,70	65 A	10	2	40	80	-15 / +80	-15 / +100	2675	3000	2,60							X	X	X				X	
576110	Nonex EF 10/2 09+19 white FG		4,40	1,90	65 A	10	2	100	140	-15 / +80	-15 / +100	2000	3000	5,30							X	X	X				X	
575230	Nonex EM 8/2 00+05 white AS FG	SR	2,00	0,50	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,30							X	X	X				X	
575700	Nonex EM 8/2 00+05 l-blue AS FG AM		2,00	0,50	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	3000	2,30							X	X	X				X	
572490	Nonex EM 8/2 07+07 white FG		3,10	0,70	65 A	8	2	80	80	-15 / +80	-15 / +100	2000	3000	3,70							X	X	X				X	
573360	Nonex EM 10/2 00+07 l-blue FG AM	SR	2,50	0,70	65 A	10	2	40	80	-15 / +80	-15 / +100	2000	3000	2,80							X	X	X					
573300	Nonex EM 10/2 00+07 white FG	SR	2,30	0,70	65 A	10	2	40	80	-15 / +80	-15 / +100	2000	3000	2,60							X	X	X				X	
573320	Nonex EM 10/2 00+07 white FG		2,50	0,70	65 A	10	2	40	80	-15 / +80	-15 / +100	2000	2700	2,80							X	X	X				X	
575730	Nonex EM 10/2 00+09 l-blue FG AM		2,60	0,90	65 A	10	2	40	80	-15 / +80	-15 / +100	2000	3000	2,80							X	X	X				X	
573400	Nonex EM 10/2 00+15 white FG	SR	3,10	1,50	65 A	10	2	60	100	-15 / +80	-15 / +100	2000	3000	3,60							X	X	X				X	
576050	Nonex EM 15/3 00+15 white FG		5,00	1,50	65 A	15	3	120	220	-15 / +80	-15 / +100	2000	3000	6,70							X	X	X				X	
MATERIAL	**PVC - top profile**																											
572862	Nonex EM 8/2 0+A15 green		2,70	1,20	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,30													X	
575703	Nonex EM 8/2 00+A18 l-blue AS FG FG		2,40	0,90	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,30							X	X	X				X	
575232	Nonex EM 8/2 00+A15 white AS FG		2,70	1,20	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,30				X			X	X	X				X	
575233	Nonex EM 8/2 00+A18 white AS FG/2,6mm	SR	2,60	1,00	65 A	8	2	25	50	-15 / +80	-15 / +100	2000	2000	2,60							X	X	X				X	
573400	Nonex EM 10/2 00+15 white FG + P20		4,90	2,80	35 A	8	2	80	100	-15 / +80	-15 / +100	2000	2000	3,90							X		X					X
MATERIAL	**PVC - bottom profile**																											
573500	Nonex EF 10/2 A18 + 07 white FG	SR	3,00	0,70	65 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,10							X	X	X				X	
576010	Nonex EF 10/2 A18+07 l-blue FG AM	SR	3,20	0,70	65 A	10	2	50	80	-15 / +80	-15 / +100	2000	3000	3,40							X	X	X				X	
573830	Nonex EF 15/3 A18+07 white FG	SR	4,30	0,70	65 A	15	3	120	120	-15 / +80	-15 / +100	2000	3000	4,70							X	X	X				X	
571990	Nonex EM 8/2 A18+05 l-blue FG AM		2,90	0,50	65 A	8	2	40	70	-15 / +80	-15 / +100	2000	2000	2,90							X	X	X				X	
570940	Nonex EM 9/3 A18+20 white FG		5,90	2,00	65 A	9	3	120	220	-15 / +80	-15 / +100	2000	3000	6,40							X	X	X				X	
MATERIAL	**POLYOLEFIN**																											
510436	Peflex ESM 5/1 02+02 transparent M1 AS FG NL		1,20	0,20	90 A	5	1	30	40	-20 / +50	-50 / +70	1500	3200	1,20				X			X	X	X				X	
510438	Peflex ESM 10/2 0+02 transparent M1 AS FG		2,10	0,20	90 A	10	2	40	60	-20 / +50	-50 / +70	1500	3200	1,90				X			X	X	X				X	
512809	Peflex ESM 10/2 0+P34 transparent AS FG NL		4,90	2,70	90 A	10	2	100	160	-20 / +50	-50 / +70	1600	1600	3,50				X			X	X	X				X	
511888	Peflex ESF 10/2 A18+05 transparent M1 AS FG		2,90	0,50	90 A	10	2	50	80	-20 / +50	-50 / +70	1500	2000	2,70				X			X	X	X				X	
514387	Polikleen ESM 8/2 0+02 transparent AS FG		2,65	0,20	90 A	8	2	150	200	-20 / +50	-10 / +70	2000	2000	2,40				X			X	X	X			C2	X	
MATERIAL	**PLETEX TPB**																											
513818	Pletex EM 10/2 0+30 red		5,30	3,00	35 A	10	2	50	50	-15 / +80	-15 / +100	1500	3000	6,10													X	
513804	Pletex EM 15/3 0+30 red		6,50	3,00	35 A	15	3		130	-15 / +80	-15 / +100	1500	3000	6,10													X	

Article No.	Description	Range	Belt thickness [mm]	Top cover thickness [mm]	Top hardness shore [°]	Force at 1% elongation [N/mm]	Number of plies	Flexing [mm]; (20°C)	Back flexing [mm]; (20°C)	Temperature range: Prolonged [°C]	Short [°C]	Standard width [mm]	Max. available width [mm]	Weight [kg/m2]	LN Low noise	CR Cold resistant	HD Hydrolysis resistant	AS Antistatic	HC High conductivity	FR Flame retardant	FDA	EC 1935/2004; EU 10/2011	Foodgrade	HR Heat resistant	AM Antimicrobial	ATEX	EF	AB
MATERIAL	**POLYURETHANE**																											
576490	Ropan EF 10/2 A18+20 (PVC) white		5,20	2,70	80 A	10	2	110	220	-15 / +60	-15 / +80	1950	1950	5,30													X	
571620	Ropan EM 10/2 00+10 (PVC) white		3,50	1,70	80 A	10	2	100	200	-15 / +60	-15 / +80	1950	2850	3,70													X	
MATERIAL	**IMPREGNATED FABRIC PU**																											
572160	Ropanol EM 6/2 00+00 (PU) AS FG NL		1,20	-	-	6	2	6	15	-30 / +90	-30 / +110	2000	2000	1,30				X			X	X	X				X	
572170	Ropanol EM 6/2 00+00 (PU) l.blue AS FG NL		1,00	-	-	6	2	6	6	-30 / +90	-30 / +110	2000	3200	1,10				X			X	X	X				X	
578180	Ropanol EM 6/2 00+00 (PU) transp.AS FG NL	SR	1,40	-	-	6	2	6	15	-20 / +90	-30 / +110	2000	2000	1,30				X			X	X	X				X	
578970	Ropanol EM 10/2 0+00 black AS HC	SR	1,60	-	-	10	2	20	20	-15 / +80	-15 / +100	2000	2850	1,70				X	X								X	
572620	Ropanol ESF 6/2 00+00 white FG NL	limited	1,60	-	-	6	2	25	60	-10 / +90	-10 / +110	2000	2000	1,90							X	X	X			C3	X	
572910	Ropanol EX 10/2 0+00 black AS		1,50	-	-	10	2	40	40	-15 / +80	-15 / +100	2000	2000	1,50				X									X	
573880	Ropanol EX 12/3 0+00 black AS		2,60	-	-	12	3	60	80	-15 / +80	-15 / +100	2000	2000	3,00	X			X									X	
MATERIAL	**POLYURETHANE - smooth**																											
572060	Ropanyl EF 4/1 0+02 white AS FG		0,80	0,20	85 A	4	1	8	30	-20 / +90	-30 / +110	2000	2000	0,76				X			X	X	X				X	
514213	Ropanyl EM 20/1 00+04 white M1 AS FG		1,90	0,40	93 A	20	1	20	80	-20 / +90	-30 / +110	3200	3250	2,00				X								C2		
575101	Ropanyl EF 10/2 00+03 white M2 FG	SR	1,60	0,30	85 A	10	2	12	40	-20 / +90	-30 / +110	2675	3000	1,80							X	X	X				X	
575411	Ropanyl EF 10/2 00+02 l.blue M2 FG AM		1,60	0,20	93 A	10	2	15	50	-20 / +90	-30 / +110	2000	3000	1,80							X	X	X				X	
575151	Ropanyl EF 10/2 0+02 black M2		1,60	0,25	85 A	10	2	12	40	-20 / +90	-30 / +110	2675	2675	1,80													X	
579910	Ropanyl DM 8/2 04+04 l.blue AS FG AM		2,00	0,40	93 A	8	2	30	30	-20 / +90	-30 / +110	2000	2000	2,20				X			X	X	X				X	
579640	Ropanyl DM 8/2 04+04 white AS FG		1,95	0,40	93 A	8	2	30	30	-20 / +90	-30 / +110	2000	2000	2,20				X			X	X	X				X	
579800	Ropanyl EM 3/1 0+02 white AS FG		0,70	0,20	85 A	3	1	6	10	-20 / +90	-30 / +110	2000	2000	0,80				X			X	X	X				X	
579801	Ropanyl EM 3/1 0+02 white M2 AS FG NL	SR	0,70	0,20	85 A	3	1	6	10	-20 / +90	-30 / +110	2000	2000	0,80				X			X	X	X				X	
579780	Ropanyl EM 3/1 00+03 light blue AS FG AM		0,80	0,30	85 A	3	1	6	10	-20 / +90	-30 / +110	2000	2000	0,80							X	X	X				X	
579781	Ropanyl EM 3/1 00+03 light blue M2 AS FG AM		0,80	0,30	85 A	3	1	6	10	-20 / +90	-30 / +110	2000	2000	0,80				X			X	X	X				X	
573999	Ropanyl EM 4/1 0+02 white M1 AS FG		0,70	0,20	93 A	4	1	8	30	-20 / +90	-30 / +110	2000	2000	0,80				X					X				X	
572250	Ropanyl EM 4/1 0+02 d.green FG NL		0,80	0,20	93 A	4	1	8	10	-20 / +90	-30 / +110	2000	3000	0,80				X			X	X	X				X	
572251	Ropanyl EM 4/1 0+02 d.green AS M2 FG		0,65	0,02	93 A	4	1	8	10	-20 / +90	-30 / +110	2000	3000	0,70							X	X	X				X	
579639	Ropanyl EM 4/1 00+03 petrol M1 AS FG		0,80	0,30	85 A	4	1	8	20	-20 / +90	-30 / +110	2000	2000	0,90				X			X	X	X				X	
577380	Ropanyl EM05 6/1 00+02 d.green AS FG																											
578171	Ropanyl EM 6/2 0+02 (PVC) d. green M2 FG		1,85	0,15	93 A	6	2	14	50	-15 / +80	-15 / +100	2000	2000	2,41							X	X	X				X	
577970	Ropanyl EM 6/2 00+02 l-blue AS FG AM	SR	1,50	0,20	93 A	6	2	14	40	-20 / +90	-30 / +110	2000	2000	1,65				X			X	X	X		X	C2	X	
577950	Ropanyl EM 6/2 00+02 white AS FG	SR	1,50	0,20	85 A	6	2	6	40	-20 / +90	-30 / +110	2000	2000	1,65				X			X	X	X			C2	X	
577951	Ropanyl EM 6/2 00+02 white M2 AS FG	SR	1,50	0,20	85 A	6	2	6	40	-20 / +90	-30 / +110	2000	2000	1,65				X			X	X	X			C2	X	X
578091	Ropanyl EM 6/2 00+05 white M2 AS FG		1,90	0,50	85 A	6	2	6	40	-20 / +90	-30 / +110	2000	2000	1,65				X			X	X	X			C2	X	
577239	Ropanyl EM04 6/2 00+03 white M1 AS FG		1,75	0,30	93 A	6	2	14	50	-20 / +90	-30 / +110	2000	2000	2,10				X			X	X	X				X	
574610	Ropanyl EM 8/2 00+02 yellow AS FG / 60D Sh		1,60	0,20	60 D	8	2	50	95	-20 / +90	-30 / +110	2000	2000	1,80				X			X	X	X			C3	X	
510679	Ropanyl EM 8/2 00+02 petrol M1 AS FG		1,40	0,20	85 A	8	2	15	40	-20 / +90	-30 / +110	1500	1900	1,60				X					X				X	
577391	Ropanyl EM 8/2 00+02 d.green M2 AS FG	SR	1,60	0,15	93 A	8	2	14	50	-20 / +90	-30 / +110	2000	2000	1,70				X			X	X	X				X	
577001	Ropanyl EM 8/2 00+02 l-blue M2 AS FG		1,60	0,20	93 A	8	2	14	50	-20 / +90	-30 / +110	2000	2000	1,70				X			X	X	X			C3	X	
577190	Ropanyl EM 8/2 00+02 white AS FG	SR	1,60	0,15	93 A	8	2	14	50	-20 / +90	-30 / +110	2000	2000	1,70				X			X	X	X				X	
577189	Ropanyl EM 8/2 00+02 white M1 FG		1,60	0,20	93 A	8	2	14	50	-20 / +90	-30 / +110	2000	2000	1,70							X	X	X				X	
573920	Ropanyl EM 8/2 00+02 white AS FG		1,35	0,20	85 A	8	2	14	50	-20 / +90	-30 / +110	2000	2000	1,50				X			X	X	X				X	
576971	Ropanyl EM 8/2 00+03 blue M2 AS FG NL		1,70	0,30	85 A	8	2	30	30	-20 / +90	-30 / +110	1500	1900	2,10				X			X	X	X				X	
576841	Ropanyl EM05 10/2 00+04 petrol M2 AS FG NL		2,40	0,40	85 A	10	2	50	90	-20 / +90	-30 / +110	2000	2000	2,90				X			X	X	X				X	
574881	Ropanyl EM 10/2 00+10 white M2 AS FG		2,60	1,00	85 A	10	2	80	120	-20 / +90	-30 / +110	2000	2000	2,70				X			X	X	X				X	
514031	Ropanyl EM 10/2 00+20 (PVC) white FG		3,80	2,00	93 A	10	2	80	120	-15 / +90	-15 / +110	1500	2000	4,50							X	X	X			C3	X	
578121	Ropanyl EM 12/2 00+02 l-blue M2 AS FG AM	SR	1,60	0,20	85 A	12	2	25	50	-20 / +90	-30 / +110	2000	2000	2,00				X			X	X	X				X	
511223	Ropanyl EX 8/2 0+03 black AS	limited	1,65	0,30	93 A	8	2	20	40	-20 / +90	-30 / +110	1500	2000	2,00	X			X									X	
514395	Ropanyl EM/K 60/3 00+04 black M2 AS		3,80	0,40	93 A	60	3	250	300	-20 / +90	-30 / +110	3000	3100	4,40				X								C2	X	

Article No.	Description	Range	Belt thickness [mm]	Top cover thickness [mm]	Top hardness shore [°]	Force at 1% elongation [N/mm]	Number of plies	Flexing [mm]; (20°C)	Back flexing [mm]; (20°C)	Temperature range: Prolonged [°C]	Short [°C]	Standard width [mm]	Max. available width [mm]	Weight [kg/m2]	LN Low noise	CR Cold resistant	HD Hydrolysis resistant	AS Antistatic	HC High conductivity	FR Flame retardant	FDA	EC 1935/2004; EU 10/2011	Foodgrade	HR Heat resistant	AM Antimicrobial	ATEX	EF	AB
MATERIAL	**POLYURETHANE - top profile**																											
578372	Ropanyl EC/M 8/2 00+A22 black AS HC LE NL		1,90	0,60	85 A	8	2	25	35	-20 / +70	-30 / +110	2000	2000	2,00				X	X								X	
579802	Ropanyl EM 3/1 0+A6 white AS FG		0,85	0,15	85 A	3	1	6	10	-20 / +90	-30 / +110	2000	2000	0,80				X			X	X	X				X	
577952	Ropanyl EM 6/2 00+A21 white AS FG	SR	1,65	0,30	85 A	6	2	6	40	-20 / +90	-30 / +110	2000	2000	1,65				X			X	X	X			C2	X	
511411	Ropanyl EM 8/2 00+P7 white AS FG		2,90	1,60	85 A	8	2	25	70	-30 / +90	-30 / +110	1500	1500	2,70							X		X				X	
514224	Ropanyl EM 10/2 0+P27 white AS FG		5,90	4,30	85 A	10	2	120	200	-20 / +90	-30 / +110	2000	2000	4,10				X			X		X				X	
510821	Ropanyl MPLY 10/1 00+P18 black	SR	3,40	1,70	93 A	10	1	50	100	-20 / +90	-30 / +110	1500	1700	3,20														X
578749	Ropanyl ESM 5/2 00+015 white M1 FG		1,20	0,15	93 A	5	2	5	15	-20 / +90	-30 / +110	2000	3000	1,30							X	X	X					
578759	Ropanyl ESM 5/2 00+015 ight blue M1 FG AM		1,20	0,15	93 A	5	2	5	15	-20 / +90	-30 / +110	2000	3000	1,30							X	X	X					
MATERIAL	**PREMIUM ROPANYL**																											
579510	Ropanyl ESM 5/2 00+015 white AS FG NF		1,30	0,15	85 A	5	2	5	20	-20 / +90	-30 / +110	2000	3000	1,40				X			X	X	X				X	
579520	Ropanyl ESM 5/2 00+015 l.blue AS FG AM NF		1,30	0,15	85 A	5	2	5	20	-20 / +90	-30 / +110	2000	3000	1,40				X			X	X	X		X		X	
579619	Ropanyl ESM 5/2 00+015 white M1 AS FG NF		1,30	0,15	85 A	5	2	5	20	-20 / +90	-30 / +110	2000	3000	1,40				X			X	X	X				X	
579629	Ropanyl ESM 5/2 00+015 l.blue M1 AS FG AM NF		1,30	0,15	85 A	5	2	5	20	-20 / +90	-30 / +110	2000	3000	1,40				X			X	X	X		X		X	
MATERIAL	**SILICONE**																											
510583	Silam EM 8/2 0+03 (PVC) white FG	SR	1,80	0,30	35 A	8	2	30	50	-15 / +80	-15 / +100	1500	3000	2,20							X		X				X	
571440	Silam EM 6/2 00+02 (PU) white AS FG	SR	1,45	0,02	30 A	6	2	6	40	-20 / +90	-30 / +110	2000	2000	1,50				X			X		X				X	