

→

Guides									
Products	CL/CLB/CLC	VL/VLB	CM	VM	CW/CWB	VW/VWB	CSB/CSC	VS	VSC
Shore Hardness	80A	80A	90A	90A	40D	40D	65A	65A	
Color	Brown/Clear	Brown/ Blue	Red	Red	White/Blue	White/Blue	Blue/Clear	Blue/Clear	
Cogged	Yes	No	Yes	No	Yes	No	Yes	No	
FDA	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Size (mm)		Add To Minimum Pulley Diameter							
Width	Height								
6	4	NR	25	NR	NR	NR	NR	NR	15
8	5.20	NR	40	NR	60	NR	NR	NR	25
10	6	35	45	50	65	55	70	22	30
13	8	40	50	60	85	60	80	28	35
17	11.50	60	75	85	115	85	110	40	50
20	12.50	NR	85	NR	125	NR	NR	NR	NR
22	14.50	75	100	110	145	110	150	NR	65

→

Special Profiles									
Products	SPN - 1000	SPY - 1000	SLW ¾	SM - 1400	TO - 9.5	TO ½	TO ⅙	SO ¾	UO - 9.5
Illustration									
Hardness	88A	86A	80A	90A	83A	83A	83A	83A	83A
Size (mm)	Top Width	15.70	15.60	19.30	30	9.50	12.70	14.30	19.20
	Height	13.60	14.50	5.50	12	3.80	5.50	6.50	8
	Bottom Width			8		3.10	8.35	9.50	7
MPD (mm)	NR	NR	40	125	30	38	70	35	50

Products	SH - 1200	TEMB - 25	TEMW - 25	TLB - 10	TLB - 15	TLW - 30	SLC - 2300	SLC - 2104
Illustration								
Hardness	100A	95A	95A	80A	80A	80A	80A	80A
Size (mm)	Top Width	17	25	25	10	15	30	30
	Height	11.50	2	2	3.80	5	17	17
	Bottom Width		4.50	4.50	3.10	6.50	22	22
MPD (mm)	230	60	60	25	30	125	100*	78

Products	Illustration	Hardness	Size (W x H)		Minimum Pulley Diameter
			Width	Height	
SH - 1300		100A/55D	16	1.70	50
SH - 1301			18	1.70	50
SH - 1302			20	1.70	50
SH - 1305			25	1.70	50
SH - 1306			14	1.70	50
SH - 1310			16	2	60
SH - 1311			18	2	60
SH - 1312			20	2	60
SH - 1313			8	2	60
SH - 1314			8	3	80
SH - 1320			10	4	95
SH - 1325			17	1.50	45

Notes: *TLW/30 - Cogged.

Food Approved Soft Material					
Products	Color	Hardness	Temperature Range	CoF (Steel)	FDA
Round Profiles	TB	72A	-40° C to +40° C	0.85	Yes
‘V’ Profiles	Transparent Blue		-40° F to +105° F		

→

Belt Coating Materials for the Food Industry							
Products	GIB*	MIB*	FEIB*	WIB*	FEMB-SP	FEMW-SP	FELB-SP
Illustration							
Description	Super Grip	Multi Grip	High Grip	Wood Grip	Spikes	Spikes	Spikes
Hardness	62A	62A	62A	62A	95A	95A	85A
Size (mm)	Width*	50	50	1524	70	1524	1524
	Thickness	4	6	4	4	2/ 2.5/ 3	2/ 2.5/ 3
CoF (Steel)	0.98	1.08	0.95	1.05	0.25	0.25	0.45
Temp. Range	-20° C to +40° C				-30° C to +60° C		-40° C to +50° C

Notes: *For Dry Applications Only.

→

Belt Coating Materials								
Products	GST - 4	MST - 6	FEST	FSTF	FSTF - ST	FSTF - ST Strips	FSTF - STX Strips	GWG - 4
Illustration								
Description	Super Grip	Multi Grip	High Grip	Foam**	Foam & High Grip Top	Foam & High Grip Strips	Foam & High Grip Double Strips	Wood Grip
Hardness	65A	65A	65A	65A	65A	65A	65A	65A
Size(mm)	Width*	50	50	1524	140	150	160	60
	Thickness	4	6	2, 3, 4, 5	14	6-12	4	4
CoF (Steel)	0.85	0.88	1.10	0.90	0.90	0.90/1.10	0.90/1.10	0.77
Temp. Range	-40° C to +55° C							

Notes: Width* - Maximum available width. **Foam - Made from 65A shore material, actual hardness is lower.



Corporate Headquarters
Sales and Manufacturing
sales@voltabelting.com

USA
Tel: +1 973 276 7905
Fax: +1 973 276 7908
Toll Free: 1-877-VOLTAUS

EUROPE
Tel: +31-546-580166
Fax: +31-546-579508

www.voltabelting.com

Volta Belting makes no warranty with respect to any of its products for a particular purpose. See Volta General Terms and Conditions.
Copyright©2011 Volta Belting Technology Ltd.



www.voltabelting.com

Conveying Solutions
‘V’ & Round Profiles

(Metric)
0 1 2

The Next Step in Belting

www.voltabelting.com